HUBER+SUHNER® DATA SHEET Between Series Adaptor: 33 BNC-SMA-50-1/1-- U



Description

Adaptor plug/jack BNC plug (male) / SMA jack (female)

Interface standards Series BNC - IEC 60169-8_MIL-STD-348A/301_CECC 22120 Series SMA -



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz
VSWR	DC - 4 GHz
	≤ 1.03 + 0.03 f (GHz)

500

0.0118 kg

compliant

Material

-65 °C to 165 °C

Mechanical Data

Number of matings Weight

Environmental Data

Operating Temperature 2002/95/EC (RoHS)

Material Data

Piece Parts

Interface - BNC plug (male) Centre contact Outer contact Body Insulator Coupling nut Gasket Interface - SMA jack (female) Centre contact Outer contact Body

Copper Beryllium Alloy Brass Brass PFA / PTFE Brass MVQ (Silicone Rubber)

Copper Beryllium Alloy Copper Beryllium Alloy Copper Beryllium Alloy PFA / PTFE

Related Documents

Ordering Information

Single package

Insulator

33 BNC-SMA-50-1/1-- UE

Surface Plating

Gold Plating (without Nickel underplating) SUCOPLATE (R) Plating SUCOPLATE (R) Plating

SUCOPLATE (R) Plating


Gold Plating (without Nickel underplating) Gold Plating (without Nickel underplating) Gold Plating (without Nickel underplating)

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions





Fax

HUBER+SUHNER

HUBER+SUHNER AG RF Technology

www.hubersuhner.com

9100 Herisau, Switzerland

Phone +41 (0)71 353 41 11 +41 (0)71 353 45 90